



Type IC, Air-Tight, Wet & Plenum

#### **DESCRIPTION**

4" Round Recessed LED With Built-In Driver Commercial Grade Quality With Architectural Design


#### FEATURES & BENEFITS

2" Deep - Install Where Ceiling Space Is Limited Type IC Rated - No Housing Required CRI 90+ for True Color Rendering Fast & Easy To Install - Save On Labor Connection Box Included - No Junction Box Needed Armored Cable - Open Plenum Rated

#### MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. Ceiling Clearance Required: 2"

### DIMENSIONS: ID 4" OD 5" Cut Out 4" to 4 1/4"



#### **AVAILABLE TRIMS**



#### ORDERING GUIDE Example: LL4RRG - 30K - WH

	CCT	Trim Finish	
LL4RRG	-	-	
2700K	27K	WH	White
3000K	30K	BK	Black
4100K	41K		

# **LL4RRG**

## 4" Round Regressed 1st Gen Plenum LED 14.5W

Project:		
Location:		
Cat #:	Qty:	
Notes:		

SPECIFICATION					
Applications	Recessed Ceiling Mount				
Energy Used	14.5 W				
Color Temperature	2700	3000	4100		
Light Output	850	860	900		
Halogen Equivalent	75 W				
Beam Angle	90°				
CRI	90 +				
Input Voltage	120V AC 50/60 Hz				
Dimming	TRIAC Dimmers 5%-100%				
Junction Box Wire Capacity	Max 5 No 12 AWG or 8 No 14 AWG				
Power Factor	0.98				
Approved Location	Insulated Ceilings, Open Plenum, Wet				
IP Rating	IP 54				
Air Tight	Yes				
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)				
Projected Life	70% Light Output at 50,000 Hours				
Certification	cULus				
Warranty	10 Year Residential / 5 Year Commercial				

ACCESSORIES Sold Separately



26" Flat Rough-In Plates - cat # RIP4



13" Flat Rough-In Plate - cat # MP4-2



13" Flanged Rough-In Plate - cat # MP4



Flanged Plate with Hanger Bars - cat # FRP4



Goof Ring OD 5 3/4"
White - cat # **GR4** Black - cat # **GR4-BK** 

COMPLIANCE





Type IC Air-Tight Open Plenum